



(19)

JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **63026961 A**

(43) Date of publication of application: **04.02.88**

(51) Int. Cl

**H01M 8/04**

(21) Application number: **61167953**

(22) Date of filing: **18.07.86**

(71) Applicant: **HITACHI LTD**

(72) Inventor: **TANAKA MASANOBU  
UOZUMI SHOHEI  
SONE ISAMU  
MIKI ATSUSHI**

**(54) FUEL CELL POWER GENERATING SYSTEM AND  
ITS OPERATION METHOD**

**(57) Abstract:**

**PURPOSE:** To make it possible to lengthen the life and to increase the performance of a fuel cell by installing a device and a method by which oxidizing agent supply shortage is temporarily brought during the operation of a fuel cell.

**CONSTITUTION:** Cell output controllers 6 are installed in cell stacks  $1_1, 1_2, \dots, 1_N$ . Flow controllers such as flow regulating valves 7 are installed in oxidizing agent supply lines 5. A controller 8 is arranged between the cell output controllers, the flow regulating valves 7 and a load current detector 3. A specific cell stack  $1_1$  of a series stack 1 is temporarily brought in an oxidizing agent shortage state during the operation of the series stack 1 without a decrease in load current of the series stack 1. By this process, the deterioration in cell performance with the passage of time is retarded and cell performance is increased.

**COPYRIGHT:** (C)1988,JPO&Japio

